



**Installation Methods:** Parquet, Herringbone, Basketweave, Brick, Ashlar

#### Product Specifications

|                     |                                                                                                               |
|---------------------|---------------------------------------------------------------------------------------------------------------|
| Construction        | Textured Loop                                                                                                 |
| Backing             | Nexus® Modular                                                                                                |
| Dye Method          | Solution Dyed                                                                                                 |
| Fiber Type          | Encore® SD Ultima® (with recycled content)                                                                    |
| Face Weight         | 20 oz./sy (678 grams/m2)                                                                                      |
| Pile Density        | 7579 oz./y3 (281.03 kg/m3)                                                                                    |
| Pattern Repeat      | N/A                                                                                                           |
| Gauge               | 1/10 (3.94 rows/cm)                                                                                           |
| Stitches Per Inch   | 10 stitches/in (3.94 stitches/cm)                                                                             |
| Standard Size       | 18" x 36" approx. (45.72cm x 91.44cm)                                                                         |
| Standard Adhesive   | Commercialon Premium Modular and LVT Adhesive                                                                 |
| Optional Adhesive   | TileTabs                                                                                                      |
| Standard Warranties | Nexus Modular<br>Commercialon Adhesive for Modular Carpet & LVT<br>Nexus FC Cushion<br>Encore SD Ultima Fiber |
| Optional Warranties | Commercialon High Moisture Adhesive for Modular Carpet and LVT<br>Tile Tabs<br>Encore® 100 Fiber              |

#### Special Technologies

|                        |          |
|------------------------|----------|
| ProSept® Antimicrobial | Optional |
| ProTex® Soil Release   | Standard |
| Sentir® Odor-Blocker   | Optional |

#### Environmental Specifications & Tests

|                        |                                    |
|------------------------|------------------------------------|
| NSF 140:               | Gold Certified                     |
| Total Recycled Content | 47.21%                             |
| Radiant Panel          | Class 1                            |
| Smoke Density          | Less than 450 flaming (ASTM E 662) |
| Static Test            | Less than 3 kv (AATCC-134)         |
| ADA Compliance         | Compliant For Accessible Routes    |
| Pill Test              | Yes                                |
| Lightfastness          | Yes                                |


#### Colorways




ALL11 Sand



ALL14 Saffron



ALL45 Denim




ALL51 Grey Tone



ALL52 Mandarin



ALL53 Fawn



ALL54 Aniline



ALL56 Verdant



ALL58 Blackened



ALL76 Taupe