



Product Specifications

Construction	Cut and Loop
Backing	Standard Back
Dye Method	Solution Dyed
Fiber Type	EF Contract SD Nylon
Face Weight	32 oz./sy (1085 grams/m2)
Pile Density	4683 oz./y3 (173.65 kg/m3)
Pattern Repeat	24.00" (w) x 26.00" (l) approx. (60.96cm x 66.04cm)
Gauge	1/8 (3.15 rows/cm)
Stitches Per Inch	12.8 stitches/in (5.04 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	Standard Back

Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	N/A Certified
Total Recycled Content	0%
Radiant Panel	Class 1
Smoke Density	Less then 450 flaming (ASTM E 662)
Static Test	Less then 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes


Colorways



ACH24 Sand



ACH25 Hazel



ACH51 Dove



ACH55 Ash



ACH74 Pearl Grey



ACH75 Taupe