Product Specifications

Construction	Textured Loop
Backing	PremierBac® Plus
Dye Method	Solution Dyed
Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	18 oz./sy (610 grams/m2)
Pile Density	10125 oz./y3 (375.44 kg/m3)
Pattern Repeat	N/A
Gauge	1/10 (3.94 rows/cm)
Stitches Per Inch	10.3 stitches/in (4.06 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	Commercialon Premium Broadloom Adhesive PremierBac Plus Encore SD Ultima Fiber
Optional Warranties	Endure Plus TitanBac Plus iLoc Encore® 100 Fiber

Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	52.5%
Radiant Panel	Class 1
Smoke Density	Less then 450 flaming (ASTM E 662)
Static Test	Less then 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways

CMT14 Golden Intui...

CMT38 Teal Harm...

CMT47 Sage Affinity

CMT49 Indigo Spirit

CMT51 Pewter Ra...

CMT56 Platinum B..

CMT58 Graphite Li...


CMT75 Mink Esse...

CMT76 Bark Integ...

CMT77 Obsidian M..


CMT98 Plum Conc...