



Product Specifications

Construction	Textured Loop
Backing	PremierBac® Plus (A)
Dye Method	Solution Dyed
Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	22 oz./sy (746 grams/m2)
Pile Density	7543 oz./y3 (279.70 kg/m3)
Pattern Repeat	6.00" (w) x .63" (l) approx. (15.24cm x 1.60cm)
Gauge	1/10 (3.94 rows/cm)
Stitches Per Inch	12.7 stitches/in (5.00 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	Encore SD Ultima Fiber
Optional Warranties	Endure Plus TitanBac Plus iLoc Encore® 100 Fiber

Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	68.9%
Radiant Panel	Class 1
Smoke Density	Less then 450 flaming (ASTM E 662)
Static Test	Less then 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes


Colorways



CNT22 Standpoint




CNT47 Framework




CNT51 Ambience



CNT52 Relation



CNT54 Perspective



CNT57 Situation