



Product Specifications

| | |
|---------------------|--|
| Construction | Patterned Scroll |
| Backing | PremierBac® Plus |
| Dye Method | Solution Dyed |
| Fiber Type | Encore® SD Nylon with TeraPlex® SD PET |
| Face Weight | 22 oz./sq yd (746 grams/m ²) |
| Pile Density | 7333 oz./sq yd (271.91 kg/m ³) |
| Pattern Repeat | N/A |
| Gauge | 1/12 (4.72 rows/cm) |
| Standard Width | 12 ft 3.66 m |
| Standard Adhesive | Commercialon Premium Carpet Adhesive |
| Standard Warranties | Commercialon Premium Broadloom Adhesive PremierBac Plus Encore SD Nylon with TeraPlex SD PET Fiber |


Special Technologies

| | |
|------------------------|----------|
| ProSept® Antimicrobial | Optional |
| ProTex® Soil Release | Standard |
| Sentir® Odor-Blocker | Optional |

Environmental Specifications & Tests

| | |
|------------------------|------------------------------------|
| NSF 140: | Gold Certified |
| Total Recycled Content | 42% |
| Radiant Panel | Class 1 |
| Smoke Density | Less than 450 flaming (ASTM E 662) |
| Static Test | Less than 3 kv (AATCC-134) |
| ADA Compliance | Compliant For Accessible Routes |
| Pill Test | Yes |
| Lightfastness | Yes |

Colorways




LND15 Ring




LND17 Hang UP




LND47 Operator




LND55 Area Code



LND57 Switchboard



LND75 Dial Tone



LND77 Redial