



Installation Methods: Ashlar, Herringbone, 1/3 Drop

Product Specifications

Wear Layer	20 mil
Thickness	2.5mm
Finish / Coating	Enhanced UV Urethane w/ Ceramic Micro Bead
Pattern Repeat	Random
Dimensions:	9" x 48"
Standard Adhesive	Commercialon Premium Modular and LVT Adhesive
Backing Class	Commercial Grade
Commercial Traffic	Heavy Commercial
Standard Warranties	15 Year LVT
Packaging	
Sq.ft. per piece / carton	3 / 48
Weight per piece / carton	2.55 (lbs) / 40.78 (lbs)
Pieces per box	16
Boxes per pallet	52
Special Technologies	
Added Antimicrobial	ZPT (Zinc Protective Technology)
Environmental Specification	s & Tests
Indoor Air Quality	FloorScore® Certified
LEED v4	Contributes to IAQ: Low Emitting Materials
End of Life	100% Recyclable
Class / ASTM F1700	Class III Printed Film Vinyl Plank - Type B (embossed)
Radiant Panel	Class 1
ADA Compliance	Compliant For Accessible Routes
ASTM F2055 (Size and Tolerance)	Passes
ASTM F386 (Thickness)	Passes
	1 40000
ASTM F1914 (Residual Indentation)	Passes
ASTM F1914 (Residual Indentation) ASTM F137 (Flexibility)	
	Passes
ASTM F137 (Flexibility)	Passes Passes
ASTM F137 (Flexibility) ASTM F2199 (Dimensional Stability)	Passes Passes Passes
ASTM F137 (Flexibility) ASTM F2199 (Dimensional Stability) ASTM F925 (Chemical Resistance)	Passes Passes Passes
ASTM F137 (Flexibility) ASTM F2199 (Dimensional Stability) ASTM F925 (Chemical Resistance) ASTM F1514 (Resistance to Heat)	Passes Passes Passes Passes
ASTM F137 (Flexibility) ASTM F2199 (Dimensional Stability) ASTM F925 (Chemical Resistance) ASTM F1514 (Resistance to Heat) ASTM F1515 (Resistance to Light)	Passes Passes Passes Passes Passes
ASTM F137 (Flexibility) ASTM F2199 (Dimensional Stability) ASTM F925 (Chemical Resistance) ASTM F1514 (Resistance to Heat) ASTM F1515 (Resistance to Light) ASTM E648 (Critical Radiant Flux)	Passes Passes Passes Passes Passes Passes Passes





001 Cafe Au Lait



002 Griffin



003 Umber



004 Urban



005 Foggy Beach



006 Phantom



