



Installation Methods: Ashlar, Herringbone, 1/3 Drop

Product Specifications

Wear Layer	20 mil
Thickness	Loose Lay 5mm
Finish / Coating	Enhanced UV Urethane w/ Ceramic Micro Bead
Pattern Repeat	Random
Dimensions:	9" x 48"
Standard Adhesive	Commercialon Premium Modular and LVT Adhesive
Backing Class	Commercial Grade
Commercial Traffic	Heavy Commercial
Standard Warranties	15 Year LVT
Packaging	
Sq.ft. per piece / carton	3 / 24
Weight per piece / carton	5.53 (lbs) / 44.25 (lbs)
Pieces per box	8
Boxes per pallet	52
Special Technologies	
Added Antimicrobial	ZPT (Zinc Protective Technology)
	-
Added Antimicrobial Environmental Specification	
Added Antimicrobial Environmental Specification	s & Tests
Added Antimicrobial Environmental Specification Indoor Air Quality LEED v4	s & Tests FloorScore® Certified
Added Antimicrobial Environmental Specification Indoor Air Quality LEED v4 End of Life	S & Tests FloorScore® Certified Contributes to IAQ: Low Emitting Materials
Added Antimicrobial Environmental Specification Indoor Air Quality LEED v4 End of Life Radiant Panel	FloorScore® Certified Contributes to IAQ: Low Emitting Materials 100% Recyclable
Added Antimicrobial Environmental Specification Indoor Air Quality LEED v4 End of Life Radiant Panel ADA Compliance	FloorScore® Certified Contributes to IAQ: Low Emitting Materials 100% Recyclable Class 1
Added Antimicrobial Environmental Specification Indoor Air Quality LEED v4 End of Life Radiant Panel ADA Compliance ASTM F2055 (Size and Tolerance)	FloorScore® Certified Contributes to IAQ: Low Emitting Materials 100% Recyclable Class 1 Compliant For Accessible Routes
Added Antimicrobial Environmental Specification Indoor Air Quality LEED v4 End of Life Radiant Panel ADA Compliance ASTM F2055 (Size and Tolerance) ASTM F386 (Thickness)	FloorScore® Certified Contributes to IAQ: Low Emitting Materials 100% Recyclable Class 1 Compliant For Accessible Routes Passes
Added Antimicrobial Environmental Specification Indoor Air Quality LEED v4 End of Life Radiant Panel ADA Compliance ASTM F2055 (Size and Tolerance) ASTM F386 (Thickness)	FloorScore® Certified Contributes to IAQ: Low Emitting Materials 100% Recyclable Class 1 Compliant For Accessible Routes Passes Passes
Added Antimicrobial Environmental Specification Indoor Air Quality LEED v4 End of Life Radiant Panel ADA Compliance ASTM F2055 (Size and Tolerance) ASTM F1914 (Residual Indentation) ASTM F137 (Flexibility)	FloorScore® Certified Contributes to IAQ: Low Emitting Materials 100% Recyclable Class 1 Compliant For Accessible Routes Passes Passes Passes
Added Antimicrobial Environmental Specification Indoor Air Quality LEED v4 End of Life Radiant Panel ADA Compliance ASTM F2055 (Size and Tolerance) ASTM F386 (Thickness) ASTM F1914 (Residual Indentation) ASTM F137 (Flexibility) ASTM F2199 (Dimensional Stability)	FloorScore® Certified Contributes to IAQ: Low Emitting Materials 100% Recyclable Class 1 Compliant For Accessible Routes Passes Passes Passes Passes Passes
Added Antimicrobial Environmental Specification Indoor Air Quality LEED v4 End of Life Radiant Panel ADA Compliance ASTM F2055 (Size and Tolerance) ASTM F386 (Thickness) ASTM F1914 (Residual Indentation) ASTM F137 (Flexibility) ASTM F2199 (Dimensional Stability) ASTM F925 (Chemical Resistance)	FloorScore® Certified Contributes to IAQ: Low Emitting Materials 100% Recyclable Class 1 Compliant For Accessible Routes Passes Passes Passes Passes Passes Passes Passes
Added Antimicrobial Environmental Specification Indoor Air Quality LEED v4 End of Life Radiant Panel ADA Compliance ASTM F2055 (Size and Tolerance) ASTM F386 (Thickness) ASTM F1914 (Residual Indentation) ASTM F137 (Flexibility) ASTM F2199 (Dimensional Stability) ASTM F925 (Chemical Resistance) ASTM F925 (Chemical Resistance)	FloorScore® Certified Contributes to IAQ: Low Emitting Materials 100% Recyclable Class 1 Compliant For Accessible Routes Passes Passes Passes Passes Passes Passes Passes Passes Passes
Added Antimicrobial Environmental Specification Indoor Air Quality LEED v4 End of Life Radiant Panel ADA Compliance ASTM F2055 (Size and Tolerance) ASTM F386 (Thickness) ASTM F1914 (Residual Indentation) ASTM F1979 (Dimensional Stability) ASTM F925 (Chemical Resistance) ASTM F1514 (Resistance to Heat) ASTM F1515 (Resistance to Light)	FloorScore® Certified Contributes to IAQ: Low Emitting Materials 100% Recyclable Class 1 Compliant For Accessible Routes Passes
Added Antimicrobial	FloorScore® Certified Contributes to IAQ: Low Emitting Materials 100% Recyclable Class 1 Compliant For Accessible Routes Passes

Colorways



001 Cafe Au Lait



002 Griffin



003 Umber



004 Urban



005 Foggy Beach



006 Phantom



007 Andiron

