



Product Specifications

Construction	Tip-Sheared Loop
Backing	PremierBac® Plus (A)
Dye Method	Solution Dyed
Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	32 oz./sy (1085 grams/m2)
Pile Density	6583 oz./y3 (244.10 kg/m3)
Pattern Repeat	.40" (w) x .50" (l) approx. (1.02cm x 1.27cm)
Gauge	1/10 (3.94 rows/cm)
Stitches Per Inch	12.66 stitches/in (4.98 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	Encore SD Ultima Fiber
Optional Warranties	Endure Plus TitanBac Plus Encore® 100 Fiber


Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	32.72%
Radiant Panel	Class 1
Smoke Density	Less then 450 flaming (ASTM E 662)
Static Test	Less then 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes


Colorways



PRC01 Parchment




PRC02 Satin




PRC03 Cashew




PRC04 Mushroom



PRC05 Fawn



PRC06 Bisque



PRC07 Canvas