



Installation Methods: Parquet, Herringbone, Basketweave, Ashlar

Product Specifications

| Troduct Specifications | |
|---|---|
| Wear Layer | 20 mil |
| Thickness | 5mm |
| Finish / Coating | Enhanced UV Urethane w/ Ceramic Micro Bead |
| Pattern Repeat | Random |
| Dimensions: | 18" x 36" |
| Standard Adhesive | Commercialon Premium Modular and LVT Adhesive |
| Backing Class | Commercial Grade |
| Commercial Traffic | Heavy Commercial |
| Standard Warranties | 15 Year LVT |
| Packaging | |
| Sq.ft. per piece / carton | 4.5 / 27 |
| Weight per piece / carton | 8.3 (lbs) / 49.77 (lbs) |
| Pieces per box | 6 |
| Boxes per pallet | 40 |
| Special Technologies | |
| Added Antimicrobial | Yes |
| Environmental Specification | s & Tests |
| Indoor Air Quality | FloorScore® Certified |
| LEED v4 | Contributes to IAQ: Low Emitting Materials |
| End of Life | 100% Recyclable |
| Class / ASTM F1700 | Class III Printed Film Vinyl Plank - Type B (embossed) |
| Radiant Panel | Class 1 |
| ADA Compliance | Compliant For Accessible Routes |
| ASTM F2055 (Size and Tolerance) | Passes |
| | |
| ASTM F386 (Thickness) | Passes |
| ASTM F386 (Thickness) ASTM F1914 (Residual Indentation) | Passes Passes |
| ASTM F1914 (Residual Indentation) | |
| | Passes |
| ASTM F1914 (Residual Indentation) ASTM F137 (Flexibility) | Passes Passes |
| ASTM F1914 (Residual Indentation) ASTM F137 (Flexibility) ASTM F2199 (Dimensional Stability) | Passes Passes |
| ASTM F1914 (Residual Indentation) ASTM F137 (Flexibility) ASTM F2199 (Dimensional Stability) ASTM F925 (Chemical Resistance) | Passes Passes Passes Passes |
| ASTM F1914 (Residual Indentation) ASTM F137 (Flexibility) ASTM F2199 (Dimensional Stability) ASTM F925 (Chemical Resistance) ASTM F1514 (Resistance to Heat) | Passes Passes Passes Passes Passes |
| ASTM F1914 (Residual Indentation) ASTM F137 (Flexibility) ASTM F2199 (Dimensional Stability) ASTM F925 (Chemical Resistance) ASTM F1514 (Resistance to Heat) ASTM F1515 (Resistance to Light) ASTM E648 (Critical Radiant Flux) | Passes Passes Passes Passes Passes Passes |
| ASTM F1914 (Residual Indentation) ASTM F137 (Flexibility) ASTM F2199 (Dimensional Stability) ASTM F925 (Chemical Resistance) ASTM F1514 (Resistance to Heat) ASTM F1515 (Resistance to Light) | Passes Passes Passes Passes Passes Passes Passes |

Colorways









004 Showing