



## Product Specifications

Construction	Textile Composite
Backing	Polyester Felt Cushion
Dye Method	Solution Dyed
Wear Layer	Polyester - applied pattern
Pattern Repeat	N/A
Total Weight	4.5 oz - 5.2 oz/ square foot
Total Thickness	.205 inches
Dimensions:	24" x 24" modules
Standard Adhesive	Kinetex Adhesive
Optional Adhesive	Kinetex PreFix
Packaging	18 modules per box (72 sq.ft)
Standard Warranties	<b>Kinetex Adhesive</b>
Optional Warranties	<b>PreFix</b>


## Special Technologies

### Environmental Specifications & Tests

Carbon Footprint:	Carbon Neutral
Recyclability:	100% Closed-loop Recyclable
NSF 140:	Platinum Certified
Total Recycled Content:	45%
Flooring Radiant Panel	Class 1
Smoke Density	Less then 450 flaming (ASTM E 662)
Static Test	Less then 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Installation Methods: Ashlar, Brick, Quarter Turn

## Colorways



SOU12 Tenor



SOU15 Accent



SOU28 Voice




SOU54 Pitch




SOU55 Noise




SOU56 Static



SOU57 Note



SOU58 Melody



SOU59 Music