



#### Product Specifications

Construction	Textured Loop
Backing	Standard Back
Dye Method	Solution Dyed
Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	26 oz./sy (882 grams/m2)
Pile Density	5318 oz./y3 (197.19 kg/m3)
Pattern Repeat	N/A
Stitches Per Inch	12.66 stitches/in (4.98 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	<b>Standard Back</b> <b>Encore SD Ultima Fiber</b>
Optional Warranties	<b>Endure Plus</b> <b>TitanBac Plus</b> <b>Encore® 100 Fiber</b>


#### Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

#### Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	25%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

#### Colorways



SRD13 Sand



SRD14 Glacier



SRD45 Seascape



SRD46 Cadet



SRD53 Dockside




SRD54 Pepper



SRD56 Dorsal




SRD58 Cauldron



SRD59 Carbon



SRD73 Toast



SRD76 Truffle



SRD77 Pinecone