EF Contract®

Sylvan | EFCSY

LVT

Product Specifications

Wear Layer	12 mil
Thickness	2mm
Finish / Coating	Enhanced UV Urethane w/ Ceramic Micro Bead
Pattern Repeat	Random
Edge Treatment	Straight
Dimensions:	7" x 48" approx. (17.78cm x 121.92cm)
Standard Adhesive	Commercialon Premium Modular and LVT Adhesive
Backing Class	Commercial Grade
Commercial Traffic	Light Commercial
Standard Warranties	7 Year LVT

Packaging

Sq.ft. per piece / carton	2.33 / 51.25
Weight per piece / carton	1.67 (lbs) / 36.72 (lbs)
Pieces per box	22
Boxes per pallet	65

Special Technologies

Added Antimicrobial	Yes

Environmental Specifications & Tests

Indoor Air Quality	FloorScore® Certified
LEED v4	Contributes to IAQ: Low Emitting Materials
End of Life	100% Recyclable
Class / ASTM F1700	Class III Printed Film Vinyl Plank - Type B (embossed)
Radiant Panel	Class 1
ADA Compliance	Compliant For Accessible Routes

ASTM F2055 (Size and Tolerance)	Passes
ASTM F386 (Thickness)	Passes
ASTM F1914 (Residual Indentation)	Passes
ASTM F137 (Flexibility)	Passes
ASTM F2199 (Dimensional Stability)	Passes
ASTM F925 (Chemical Resistance)	Passes
ASTM F1514 (Resistance to Heat)	Passes
ASTM F1515 (Resistance to Light)	Passes
ASTM E648 (Critical Radiant Flux)	Passes
ASTM E662 (Optical Smoke Density)	Passes
ASTM C1028 (Slip Resistance)	Passes
ASTM F970 (Static Load)	Passes

Colorways

001 Linden

002 Lakemont

003 Cuyler

004 Hamilton

005 Thornton

006 Pentz

007 Waugh

008 Tibbs

009 Riverbend

010 Vernon

EF Contract®

www.efcontractflooring.com