



Installation Methods: Brick, Monolithic, Ashlar, Quarter Turn

Product Specifications

|                     |                                                                                                                                             |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| Construction        | Patterned Scroll                                                                                                                            |
| Backing             | Nexus® Modular                                                                                                                              |
| Dye Method          | Solution Dyed                                                                                                                               |
| Fiber Type          | Encore® SD Ultima® (with recycled content)                                                                                                  |
| Face Weight         | 15 oz./sy (509 grams/m2)                                                                                                                    |
| Pile Density        | 6585 oz./y3 (244.18 kg/m3)                                                                                                                  |
| Pattern Repeat      | N/A                                                                                                                                         |
| Gauge               | 1/12 (4.72 rows/cm)                                                                                                                         |
| Stitches Per Inch   | 11.8 stitches/in (4.65 stitches/cm)                                                                                                         |
| Standard Size       | 24" x 24" approx. (60.96cm x 60.96cm)                                                                                                       |
| Standard Adhesive   | Commercialon Premium Modular and LVT Adhesive                                                                                               |
| Optional Adhesive   | TileTabs                                                                                                                                    |
| Standard Warranties | Nexus Modular<br>Commercialon Adhesive for Modular Carpet & LVT<br>Encore SD Ultima Fiber                                                   |
| Optional Warranties | Advance Modular Backing<br>Nexus Cushion Modular Adhesive<br>Advance Modular Adhesive<br>Tile Tabs<br>Nexus FC Cushion<br>Encore® 100 Fiber |


Special Technologies

|                        |          |
|------------------------|----------|
| ProSept® Antimicrobial | Optional |
| ProTex® Soil Release   | Standard |
| Sentir® Odor-Blocker   | Optional |


Environmental Specifications & Tests

|                        |                                    |
|------------------------|------------------------------------|
| NSF 140:               | Gold Certified                     |
| Total Recycled Content | 46.5%                              |
| Radiant Panel          | Class 1                            |
| Smoke Density          | Less then 450 flaming (ASTM E 662) |
| Static Test            | Less then 3 kv (AATCC-134)         |
| ADA Compliance         | Compliant For Accessible Routes    |
| Pill Test              | Yes                                |
| Lightfastness          | Yes                                |


Colorways




TER47 Nightfall



TER52 Strand




TER53 Smoke




TER54 Grayness




TER55 Riverstone




TER56 Shale




TER59 Blackstone



TER73 Adobe



TER76 Earth



TER84 Crimson