



### Product Specifications

<b>Construction</b>	Direct Digital Print & Emboss SPC
<b>Backing</b>	DLVT Attached Cushion
<b>Wear Layer</b>	Equivalent to 20 mil
<b>Attached Pad</b>	1.0 mm XPO
<b>Locking Mechanism</b>	One2Click®
<b>Thickness</b>	5mm
<b>Finish / Coating</b>	Evertuff Clearcoat®
<b>Pattern</b>	35 Unique Planks
<b>Dimensions:</b>	7" x 48" approx. (17.78cm x 121.92cm)
<b>Backing Class</b>	Commercial Grade
<b>Commercial Traffic</b>	Light Commercial
<b>Standard Warranties</b>	<b>Rigid Core</b>

### Packaging

<b>Sq.ft. per piece / carton</b>	2.22 / 22.17
<b>Weight per piece / carton</b>	3.75 (lbs) / 37.51 (lbs)
<b>Pieces per box</b>	10
<b>Boxes per pallet</b>	50

### Special Technologies

#### Environmental Specifications & Tests

<b>Indoor Air Quality</b>	FloorScore® Certified
<b>LEED v4</b>	Contributes to IAQ: Low Emitting Materials
<b>End of Life</b>	100% Recyclable
<b>Radiant Panel</b>	Class 1
<b>ADA Compliance</b>	Compliant For Accessible Routes

<b>ASTM F2055 (Size and Tolerance)</b>	Passes
<b>ASTM F386 (Thickness)</b>	Passes
<b>ASTM F1914 (Residual Indentation)</b>	Passes
<b>ASTM F137 (Flexibility)</b>	Passes
<b>ASTM F2199 (Dimensional Stability)</b>	Passes
<b>ASTM F925 (Chemical Resistance)</b>	Passes
<b>ASTM F1514 (Resistance to Heat)</b>	Passes
<b>ASTM F1515 (Resistance to Light)</b>	Passes
<b>ASTM E648 (Critical Radiant Flux)</b>	Passes
<b>ASTM E662 (Optical Smoke Density)</b>	Passes
<b>ASTM C1028 (Slip Resistance)</b>	Passes
<b>ASTM F970 (Static Load)</b>	Passes

Colorways




008 Superior



009 Borah



010 Tetons



011 Sequoia



012 Appalachian



013 Pinhoti



014 Pinhook

 EF Contract

[www.efcontractflooring.com](http://www.efcontractflooring.com)