**Installation Methods:** Brick, Ashlar, Quarter Turn

## Product Specifications

| | |
|---|---|
| **Construction** | Patterned Loop |
| **Backing** | Nexus® Modular |
| **Dye Method** | Solution Dyed |
| **Fiber Type** | Encore® SD (with recycled content) |
| **Face Weight** | 18 oz./sy (610 grams/m2) |
| **Pile Density** | 7867 oz./y3 (291.71 kg/m3) |
| **Pattern Repeat** | N/A |
| **Gauge** | 1/12 (4.72 rows/cm) |
| **Stitches Per Inch** | 10 stitches/in (3.94 stitches/cm) |
| **Standard Size** | 24" x 24" approx. (60.96cm x 60.96cm) |
| **Standard Adhesive** | Commercialon Premium Modular and LVT Adhesive |
| **Optional Adhesive** | TileTabs |
| **Standard Warranties** | Nexus Modular<br>Commercialon Adhesive for Modular Carpet & LVT |
| **Optional Warranties** | Advance Modular Backing<br>Nexus Cushion Modular Adhesive<br>Advance Modular Adhesive<br>Tile Tabs<br>Encore® 100 Fiber |

## Special Technologies

## Environmental Specifications & Tests

| | |
|---|---|
| **NSF 140:** | Gold Certified |
| **Total Recycled Content** | 40.5% |
| **Radiant Panel** | Class 1 |
| **Smoke Density** | Less then 450 flaming (ASTM E 662) |
| **Static Test** | Less then 3 kv (AATCC-134) |
| **ADA Compliance** | Compliant For Accessible Routes |
| **Pill Test** | Yes |
| **Lightfastness** | Yes |

## Colorways

VIS01 Petal Line

VIS02 Gridstone

VIS03 Axial

VIS04 Framework

VIS05 Wild Mist

VIS06 Basalt

VIS07 Lattice

VIS08 Slate


VIS09 Canopy

VIS10 Drift


VIS11 Core



VIS12 Base