Installation Methods: Brick, Monolithic, Ashlar, Quarter Turn

Product Specifications

Construction	Textured Loop
Backing	Nexus® Modular
Dye Method	Solution Dyed
Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	22 oz./sy (746 grams/m2)
Pile Density	9290 oz./y3 (344.48 kg/m3)
Pattern Repeat	N/A
Gauge	1/10 (3.94 rows/cm)
Standard Size	24" x 24" approx. (60.96cm x 60.96cm)
Standard Adhesive	Commercialon Premium Modular and LVT Adhesive
Optional Adhesive	TileTabs
Standard Warranties	Nexus Modular Commercialon Adhesive for Modular Carpet & LVT Encore SD Ultima Fiber
Optional Warranties	Advance Modular Backing Nexus Cushion Modular Adhesive Advance Modular Adhesive Tile Tabs Nexus FC Cushion Encore® 100 Fiber

Special Technologies

Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	44.8%
Radiant Panel	Class 1
Smoke Density	Less then 450 flaming (ASTM E 662)
Static Test	Less then 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways

WTC11 Bone White

WTC15 Gamboge

WTC33 Sap Green

WTC35 Celadon

WTC37 Turquoise

WTC38 Phthalo Gr...

WTC44 Cerulean

WTC46 Lapiz

WTC47 Ultramarine

WTC49 Dark Cobalt

WTC51 Smoke

WTC54 Payne's Gr...

WTC56 Lead Gray

WTC59 Soot Black

WTC68 Rose Madd...

WTC76 Raw Sienna

WTC78 Umber

WTC86 Vermillion

WTC88 Scarlet Red

WTC98 Mars Violet