Melange

LVT

EF Contract®



FRONT COVER: MELANGE - GRIFFIN

Melange

A brilliant interplay of unexpected and nuanced elements of wood, stone and concrete, Melange's contrasting textures of geodes and sandstone meld with weathered woodgrains. Its subdued palette of seven earthy colorations will create a cohesive, artfully realized space.

MELANGE - UMBER



MELANGE - FOGGY BEACH

9" X 48"

MELANGE

EFCM2001 | CAFÉ AU LAIT
(AVAILABLE IN EFCM5001)

EFCM2002 | GRIFFIN
(AVAILABLE IN EFCM5002)

EFCM2003 | UMBER
(AVAILABLE IN EFCM5003)

EFCM2004 | URBAN
(AVAILABLE IN EFCM5004)

EFCM2005 | FOGGY BEACH
(AVAILABLE IN EFCM5005)

EFCM2006 | PHANTOM
(AVAILABLE IN EFCM5006)

EFCM2007 | ANDIRON
(AVAILABLE IN EFCM5007)

SCAN ME!

Scan to order samples or check inventory.

COORDINATING PALETTES

Beyond the beauty of individual products, EF Contract's flooring **coordinate effortlessly** across all of our product platforms - modular carpet tile, broadloom, LVT and Kinetex textile composite flooring. This offering enables you to blend a range of designs to create **palettes** that meet the demands of each unique space.

1	VEIL - SCREEN	VLT25	MODULAR
2	PLEAT - RICE PAPER	PLE12	MODULAR
3	VESTIGE - ASHEN	VES14	KINETEX
4	CONTEXT - STANDPOINT	CNT22	BROADLOOM
5	MELANGE - CAFÉ AU LAIT	EFCML001	LVT
6	INTRIGUE - ENTHRALL	ITR75	KINETEX
7	IMMERSE - OCHRE	IMM23	MODULAR
8	BATISTE II - FEDORA	BTT74	MODULAR
9	CREASE - BUTCHER PAPER	CRE76	MODULAR

Sustainably Sound

EF Contract believes true sustainability requires full attention to the potential impacts of every aspect of our business. In accordance with our mission of waste reduction, all EF Contract LVT products are 100% recyclable.

You can rest assured that health is also a top priority and all EF Contract LVT products are FloorScore Certified.

©2021 Engineered Floors LLC - This unique design is protected under the U.S. Copyright Act of 1976. Any unauthorized copying or duplication of this design constitutes copyright infringement in violation of federal law.

These photographs are representations of the installation for this modular product. Your modular installation may look different than these photos depending upon individual tile placement, lighting, and overall space layout, including furnishings. Final tile placement and the resulting visual is thus the customer's, and not EF Contract's responsibility.

To learn more, visit:

EFCONTRACTFLOORING.COM



1 Protective UV Cured Urethane With Ceramic Bead And Antimicrobial

2 20mil Wear Layer

3 High Definition Print Film

4 Impact Resistant Core Layer

5 Foundational Base Layer

MELANGE PRODUCT SPECIFICATIONS

STYLE	MELANGE | EFCM2	MELANGE | EFCM5
THICKNESS	2.5MM	5MM
WEAR LAYER	20MIL	20MIL
FINISH/COATING	ENHANCED UV URETHANE W/ CERAMIC MICRO BEAD	ENHANCED UV URETHANE W/ CERAMIC MICRO BEAD
PATTERN REPEAT	RANDOM	RANDOM
NOMINAL DIMENSIONS (INCHES)	9" X 48"	9" X 48"
STANDARD ADHESIVE	COMMERCIALON PREMIUM MODULAR AND LVT ADHESIVE	COMMERCIALON PREMIUM MODULAR AND LVT ADHESIVE
BACKING CLASS	COMMERCIAL GRADE	COMMERCIAL GRADE
COMMERCIAL TRAFFIC	HEAVY COMMERCIAL	HEAVY COMMERCIAL
STANDARD WARRANTIES	15 YEAR LVT	15 YEAR LVT
PACKAGING		
SQ.FT. PER CARTON	48	24
PIECES PER BOX	16	8
BOXES PER PALLET	52	52
SPECIAL TECHNOLOGIES		
ANTIMICROBIAL	YES	YES
ENVIRONMENTAL SPECIFICATIONS & TESTS		
INDOOR AIR QUALITY	FLOORSCORE® CERTIFIED	FLOORSCORE® CERTIFIED
LEED V4	CONTRIBUTES TO IAQ: LOW EMITTING MATERIALS	CONTRIBUTES TO IAQ: LOW EMITTING MATERIALS
END OF LIFE	100% RECYCLABLE	100% RECYCLABLE
CLASS / ASTM F1700	CLASS III PRINTED FILM VINYL PLANK - TYPE B (EMBOSSED)	CLASS III PRINTED FILM VINYL PLANK - TYPE B (EMBOSSED)
FLOORING RADIANT PANEL	CLASS 1	CLASS 1
ADA COMPLIANCE	COMPLIANT FOR ACCESSIBLE ROUTES	COMPLIANT FOR ACCESSIBLE ROUTES
PERFORMANCE		
SIZE AND TOLERANCE	ASTM F2055 - PASSES	ASTM F2055 - PASSES
THICKNESS	ASTM F386 - PASSES	ASTM F386 - PASSES
RESIDUAL INDENTATION	ASTM F1914 - PASSES	ASTM F1914 - PASSES
FLEXIBILITY	ASTM F137 - PASSES	ASTM F137 - PASSES
DIMENSIONAL STABILITY	ASTM F2199 - PASSES	ASTM F2199 - PASSES
CHEMICAL RESISTANCE	ASTM F925 - PASSES	ASTM F925 - PASSES
RESISTANCE TO HEAT	ASTM F1514 - PASSES	ASTM F1514 - PASSES
RESISTANCE TO LIGHT	ASTM F1515 - PASSES	ASTM F1515 - PASSES
CRITICAL RADIANT FLUX	ASTM E648 - CLASS 1	ASTM E648 - CLASS 1
OPTICAL SMOKE DENSITY	ASTM E662 -PASSES	ASTM E662 - PASSES
SLIP RESISTANCE	ASTM C1028 - PASSES	ASTM C1028 - PASSES
STATIC LOAD	ASTM F970 - PASSES	ASTM F970 - PASSES
RECOMMENDED INSTALLATION METHODS	1/3 DROP, ASHLAR, HERRINGBONE	

EF Contract®

PO Box 2207
Dalton, Georgia 30722
U.S.A.

800.451.1250
efcontractflooring.com