

Commercialon® Premium Carpet Seam Sealer

Product Identification

Product Class: Aqueous Adhesive
 Product Name: Premium Carpet Seam Sealer
 Trade Name: Commercialon® Seam Sealer

Hazardous Ingredients

None known.
**All components of this product appear on the Inventory of Chemical Substances published by the U.S. Environmental Protection Agency (EPA) under the authority of the Toxic Substances Control Act (TSCA).*

Physical Data

Boiling Point: 212° F
 Vapor Density: Same as water.
 Evaporation Rate: Same as water.
 Appearance and Odor: White, milky opaque low odor
 Weight per Gallon: 8.4 lbs.
 Percent Volatile by Weight: 29-32% (as water)
 Solubility in Water: Dispersible
 V.O.C. (Calculated): "zero" grams/liter

Fire and Explosion Hazard Data

Flammable Limits: Non-flammable
 Flash Point: > 212 deg. F.
 Flammability Classification: OSHA: None, DOT: None
 Extinguishing Media: CO2, chemical foam, water fog

Special Fire Fighting Features

Wear self-contained breathing gear when in confined area.

Health Hazard Data

Threshold Limit Value: Not established
 Effects of Overexposure: No known chronic overexposure effects.

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	B

Emergency and First Aid Procedure

Eye contact may cause irritation. In case of eye contact, flush with water for 10-15 minutes. If irritation persists, consult a physician.

Skin Contact: prolonged contact may cause slight irritation of the skin. Wash with soap and water. If swallowed, consult a physician.

Inhalation: if symptomatic, move to fresh air. Get medical attention if symptoms occur.

Reactivity Data

Conditions to Avoid: Excessive heat or cold.
 Stability: Stable.
 Incompatibility: None known.
 Hazardous Decomposition Products: None known; Normal (CO2, CO).
 Hazardous Polymerization: Will not occur.

Precautions for Handling and Use

Ventilation: Local ventilation.
 Protective Gloves: Recommended.
 Eye Protection: Safety glasses.
 Hygienic Practices: Wash with soap and water after exposure.
 Respiratory Protection: Not required with adequate ventilation.
 Other Protective Equipment: None.
 Spills: Cover small spills with inert absorbent, then sweep up and place in waste disposal container. Dispose of in accordance with Federal, State and Local regulations.

Special Precautions/Other Comments

Precautions to be taken in handling and storing: Store inside at a temperature of 60° - 100° F. Do not allow product to freeze.
 Other precautions: None

Transportation Data

D.O.T. Hazard Class: Unregulated

24-Hour Emergency

Chemtrec: 800 424 9300
 J+J Flooring Group Customer Relations
 Department at 800.241.4586
 EF Contract Customer Relations
 Department at 800.451.1250
 Pentz Commercial Technical Relations
 Department at 866.706.974